

CMP

THE DIFFERENCE IS CLEAR




DEL:AOP SPA 2
SPA ADVANCED OXIDATION PROCESS

THE MOST ADVANCED WAY TO KEEP PORTABLE SPA WATER CLEAN AND HEALTHY WITH REDUCED CHEMICAL DEMAND

Science has shown that a hot tub will never be cleaner than it is with AOP. Combining two powerful cleaning technologies—UV-C and Ozone—DEL AOP® Spa 2 offers superior oxidation to rid spas of 99.9%* of certain contaminants including those chemical sanitizers alone can't break down.

THE BEST GOT BETTER

UV chamber doubled in size for a longer, more potent dose of germicidal UV-C rays, for performance that exceeds competition**



INDUSTRY INNOVATOR

As the first to put AOP to use in hot tubs, DEL products are generations ahead

QUICK & EASY INSTALLATION

All-in-one design with built-in Venturi injector makes installation easy



ADDITIONAL FEATURES

- The synergy of Ozone + UV-C creates hydroxyl radicals for the cleanest hot tub possible
- Enhances filtration by oxidizing organic contaminants to filter out more efficiently
- Certified by Underwriters Laboratories (UL)
- Fits any portable hot tub or swim spa up to 2500 gallons

Legal and Footnotes

*Based on third party testing in accordance with relevant ISO standards for microorganisms tested: Escherichia coli, Enterococcus spp., Pseudomonas aeruginosa, Staphylococcus aureus.

**Based on third party comparison testing of DEL AOP Spa 2 vs. Balboa Waveo₃ne™ in accordance with relevant ISO standards for microorganisms tested: Escherichia coli, Enterococcus spp., Pseudomonas aeruginosa, Staphylococcus aureus.

SPECIFICATIONS

Global Power Ratings	120 - 240V 50/60Hz 271 - 207mA 25W
Enclosure	IPX5
Operating Water Temp	41 - 104°F 5 - 40°C Max
Operating Pressure	30 PSI Max
Flow Rate	4 - 12 GPM

Part Number
55000-000-909 for Ribbed Barb
55007-000-909 for Smooth Barb

A Fluidra Brand | C-M-P.com | 1.800.822.7933

©2025 Fluidra. All rights reserved. The trademarks and trade names used herein are the property of their respective owners. 82576_SL



82576_SL