Brilliant Wonders LED LIGHTING

BRILLIANT WONDERS REVIEW



Patent Pending LED Waterfall

The Only LED Bubbler for Vinyl, Fiberglass, or Gunite

Industry Leading LED Products

Growing Brand Awareness









BRILLIANT WONDERS 2016



Exciting New LED Products

CMP Smart Sync Innovation

Complete Pool LED Design Solutions





BRILLIANT WONDERS 2016



LED Bubbler with Smart Sync

LED Light with Smart Sync

Smart Sync LED Waterfall Control





SMART SYNC TECHNOLOGY





WHAT IS SMART SYNC TECHNOLOGY



One LED lighting system for every pool

Smart Sync is Simple: It just works

Proprietary technology synchronizes all Brilliant Wonders products

Synchronize with Jandy, Pentair & Hayward control systems





SMART SYNC TOP QUESTIONS

Is the old power supply or control also required - No Will Smart Sync work with our remote control -No What program or style is CMP style - Jandy





H-Style TOP QUESTIONS

How do I get H-Style parts? - Just append part number Is there any other special part I need to synchronize? - No Does Smart Sync work with Hayward network controls- No





P-Style TOP QUESTIONS

How do I get P-Style parts? - Just append part number Is there any other special part I need to synchronize? - No







SMART SYNC LED WATERFALL CONTROL



One Smart Sync control for all styles

Controls up to ten total feet of LED waterfalls

Uses industry standard 12VAC pool transformers

Simple to install and wire





SMART SYNC LED WATERFALL CONTROL



Control dial for setting in the field

For LED Waterfall Only

ETL Certified

Not Compatible with Previous LED Waterfall Controls





SMART SYNC LED WATERFALL CONTROL



One control per 10ft of waterfalls

Use multiple controls for over 10ft

Rated Max 3.0A @ 12VAC

12VAC transformer always required





SMART SYNC CONTROL MANUAL




STEP 1

Using a flathead screwdriver, turn the dial until the desired program is selected.

| Dial Setting | Style |
|--------------|-------------|
| 1 | CMP/J-Style |
| 2 | H-Style |
| 3 | P-Style |

NOTICE

This product is for use with the Brilliant Wonders LED Waterfall only.




STEP 2

Mount Smart Sync control box in a NEMA approved weatherproof enclosure (mounting screws not included).

Recommend CMP Part #: 25650-100-210






STEP 3

Attach wires to control box by pressing button and inserting wires. Follow wiring diagram.









:b0615

CUSTOM MOLDED PRODUCTS | 36 HERRING ROAD, NEWNAN, GA 30265 | WWW.C-M-P.COM

Detailed installation and safety information

Easy to read graphics and images

Also available 24/7 online at c-m-p. com/downloads





SMART SYNC CONTROL MANUAL

CMP/J-STYLE SYNC INSTRUCTIONS

To operate the light and change colors:

- Turn the light ON. The first time the light is turned on, the color sequence will begin with Alpine White. To change color, turn light OFF then back ON within three (3) seconds. Continue turning OFF and ON until the desired light color mode is reached.
- When the light is turned off for more than seven (7) seconds, it will remain in the color mode that was currently active when the light was turned off.
- To RESET the light to the beginning color sequence (Alpine White), turn the light OFF, wait four (4) to six (6) seconds, then turn the light ON.

H-STYLE SYNC INSTRUCTIONS

To operate the light and change colors:

• The H-Style lights are operated through power-cycling; a method of changing modes which requires no special controller or interface. To activate the lights simply turn the power switch ON. To advance to the next programmed light mode, turn the switch OFF then back ON within ten (10) seconds. Whenever the lights have been off for more than sixty (60) seconds, and it is first turned on, they will come on white for 15 seconds, then go back to the last programmed light mode it was running before being powered off.

To sync the light with additional H-STYLE lights:

 The H-Style lights can easily be synced with additional H-Style lights. All lights should be wired to the same switch, this should automatically sync the lights. If the lights get out of sync on the same switch: turn the switch OFF, then wait between eleven (11) and fourteen (14) seconds and turn the switch back ON.
 When the lights come back on, they should enter program mode number one (1) and be synchronized.

P-STYLE COLOR SELECTION AND SYNC INSTRUCTIONS

To operate the light and change colors:

jh0615

- The P-Style lights can be controlled using a standard wall-mount light switch. Multiple lights can be
 connected via a junction box to a single switch so that all lights can be switched ON and OFF together. "P"
 Style Lights are controlled by cycling the AC power from a standard wall switch. By turning the switch ON
 and OFF a specific number of times, the light activates one of the seven (7) light show modes, fixed colors,
 and enables the "Hold" and "Recall" feature.
- No special sync instructions are required for P-Style lights. The lights will re-sync automatically each time
 they are powered on.

For the most recent instructions, videos and product information visit www.c-m-p.com



CUSTOM MOLDED PRODUCTS | 36 HERRING ROAD, NEWNAN, GA 30265 | WWW.C-M-P.COM


Simple synchronization steps

Steps are the same as those for OEM lighting

Sync Steps are required for installations with no master pool control system








The Smart Sync Control is easy and simple to set up. Simple connect waterfalls to the control, and then to a 12VAC pool transformer. All Smart Sync lighting and compatible controls connected to the same transformer will sync correctly.

For multiple waterfalls, simply connect at a junction box before the Smart Sync control. For over ten total feet of waterfalls, use multiple Smart Sync controls in parallel, and connect to the same transformer. Other LED lighting can also be installed in parallel to the same transformer.



SIMPLE INTEGRATION WITH ALL OTHER POOL LIGHTING



Integrate with all other pool lighting with no special requirements. Simply connect the same as any other LED pool lighting. One line per component connects to a 12VAC pool transformer. All Smart Sync products connected to the same transformer will synchronize. Connect the transformer to pool controls for complete system integration.





2016 LED BUBBLER



Built-in Smart Sync Technology

New Cree LED Lighting







2016 LED BUBBLER



Built-in, no external controls


Order CMP/J-Style, H-Style or P-Style

Synchronize with CMP Lighting or order to match OEM controls





2016 LED BUBBLER





Fewer LEDs required (6) for the same level of light output

More efficient output with less heat for longer LED life





LED BUBBLER TOP QUESTIONS

Can the new bubbler replace old ones in field - Yes Will the color shows match with old units? - No When will new design be available? - Jan 2016











Brilliant Wonders



IP68 Waterproof Quick Disconnect

Built-in Smart Sync technology

Interchangeable designer faceplates

High performance Cree LED Lighting





QUICK DISCONNECT



Industry first product feature

Enables fast service and repair

Easy Winterization

ETL Certified connection







Built-in, no external controls

Order CMP/J-Style, H-Style or P-Style

Synchronize with CMP Lighting or order to match OEM controls





DESIGNER FACEPLATES



Fits any standard 1.5" fitting

Color, stainless steel or color accent

Designed to look amazing day & night

Consumer targeted industrial design





HIGH PERFORMANCE LIGHTING



Fine tuned for output & longevity

Comparable brightness to other brands

RGBW for true white light output

Smooth blending light pattern with no hard edges or color banding





1.5" LED LIGHT KIT

Kit includes LED light, white faceplate, cord & tool Color, stainless steel & SS accent faceplates available







HOW TO ORDER SMART SYNC

Append part number with "H" or "P" Standard CMP style matches Jandy

11 or 8 Watt color (No Smart Sync needed for white)

| | BRILLIANT WONDERS® 1.5" LED LIGHT (CMP / J-STYLE) | | | | | | | | | | |
|---|---|---|---|---|--|--------------------------------|--|--|--|--|--|
| REF | 25 FT KIT | 50 FT KIT | 100 FT KIT | 150 FT KIT | DESCRIPTION | ENERGY | | | | | |
| A A A | 25503-560-025 25503-520-025 25503-500-025 | 25503-560-050 25503-520-050 25503-500-050 | 25503-560-100 25503-520-100 25503-500-100 | 25503-560-150 25503-520-150 25503-500-150 | 11C BRILLIANT COLOR LIGHT KIT 8C BRILLIANT COLOR LIGHT KIT BRILLIANT WHITE LIGHT KIT | 11 WATTS 8 WATTS 5 WATTS | | | | | |
| | BRILLIANT WONDERS® 1.5" LED LIGHT (P-STYLE) | | | | | | | | | | |
| A A | 25503-560-025P 25503-520-025P | 25503-560-050P 25503-520-050P | 25503-560-100P 25503-520-100P | 25503-560-150P 25503-520-150P | 11C BRILLIANT COLOR LIGHT KIT, P-STYLE 8C BRILLIANT COLOR LIGHT KIT, P-STYLE | 11 WATTS 8 WATTS | | | | | |
| BRILLIANT WONDERS® 1.5" LED LIGHT (H-STYLE) | | | | | | | | | | | |
| A A | 25503-560-025H 25503-520-025H | 25503-560-050H 25503-520-050H | 25503-560-100H 25503-520-100H | 25503-560-150H 25503-520-150H | 11C BRILLIANT COLOR LIGHT KIT, H-STYLE 8C BRILLIANT COLOR LIGHT KIT, H-STYLE | 11 WATTS 8 WATTS | | | | | |

1.5" LED LIGHT FACEPLATES

Every kit will include a standard white faceplate Designer faceplates sold separately







| _ | | - | | | | _ | _ | | _ | _ | |
|---|----|----------|-----------|-----|---|-----|---|----------|---|---|---|
| - | | ` | Λ | NI | | . ` | • | ` | - | _ | |
| | υL | JI | Αl | I N | ᄔ | | | . J | _ | L | ᆫ |
| | | _ | - | _ | | | | _ | | | _ |

| | BRILLIANT WONDERS® 1.5" LED LIGHT FACEPLATE | | | | | | | | | | |
|-----|---|---------------|---------------|---------------|---------------|---------------|---------------|-----------------|--|--|--|
| REF | WHITE/OTHER | GRAY | BLACK | DARK GRAY | LIGHT BLUE | DARK BLUE | TAN | DESCRIPTION | | | |
| В | 25503-510-000 | 25503-511-000 | 25503-514-000 | 25503-517-000 | 25503-559-000 | 25503-569-000 | 25503-519-000 | FULL COLOR | | | |
| С | 25503-510-200 | _ | _ | _ | _ | _ | _ | STAINLESS STEEL | | | |
| D | 25503-510-220 | 25503-511-220 | 25503-514-220 | 25503-517-220 | 25503-559-220 | 25503-569-220 | 25503-519-220 | SS COLOR ACCENT | | | |

TECHNICAL SPECIFICATIONS

ETL CERTIFIED

11, 8 or 5 watt

No bonding or grounding

12VAC transformer required

Water cooled

Heat conductive PPC body

Color or White LED

4" minimum depth

Wall or floor installation

Install in any 1.5" fitting

Vinyl, gunite or fiberglass pools

Bayonet quarter turn installation

4.5" deep light body






SMART SYNC CONTROL MANUAL



25503-500-000 25503-520-000 (P-Style and H-Style) 25503-560-000 (P-Style and H-Style) Cord Lengths Available: 25', 50', 100', 150'







LED WATERFALL | LED BUBBLER | LED LIGHTS | LED LAMINAR

CMP DOCUMENT 11120-000-000

CUSTOM MOLDED PRODUCTS | 36 HERRING ROAD, NEWNAN, GA 30265 | WWW.C-M-P.COM

Detailed installation and safety information

Easy to read graphics and images

Available online 24/7 at c-m-p. com/downloads





1.5" LED LIGHT MANUAL


3. INSTALLATION INSTRUCTIONS

STEP 1

The light must be installed in or on a wall of the pool (or water feature) with the top of the lens opening no less than 4 inches (10.16 cm) below normal water level of the pool. For vertical installations on benches, swim outs and fountains the depth of the light underwater must still be no less than 4 inches.

NOTE: Requires the use of a 1.5" threaded wall fitting.


NOTE: 12" minimum of 1.5" pipe to accommodate the LED Light. Then 1" pipe to control box with sweeps only, no 90° bends.



STEP 2

Install supplied 2-conductor electric cord through the conduit outlet of the wall into the conduit and up to the location of the 12VAC pool/spa transformer. Cut off excess cord installing appropriate service length.

NOTICE Allow 18"-24" extra slack in the cord on the 12VAC pool transformer end for future service of the LED light.



An example of an approved pool transformer is the Intermatic model PX-100 or PX-300. Refer to Wire Gauge and Wire Length guide for proper wire gauge size in reference to the use of Junction Box installations.

NOTE: Brilliant Wonders 1.5" LED Light can be used with any UL Listed, outdoor rated, 12VAC transformer provided the wattage and amperage is not exceeded by the total wattage and amperage in use.

IP68 Connector: Rated 39 inches

Max Install Depth (Floor): 2 feet

Max Install Depth (Wall): 3 feet

Leave slack at transformer for light service or replacement





HOW MANY LIGHTS?

THERE ARE MANY POOL LIGHTING VARIABLES


- Ambient light
- Pool materials
- Placement
- Pool geometry

- Pool dimensions
- Color or material of pool liner
- Cleanliness of pool
- Etc.





RECOMMENDED LIGHTING STYLE



Evenly distributed light is a primary benefit


Designed for even illumination as well as coves, steps, swim-outs, etc

8W light designed for smaller accent areas

Enhances lighting design for backyard pools

Not designed to be a 1:1 replacement for a single large traditional pool light

16 X 32 SUGGESTED LIGHTS



estimates based on typical pool installations, conditions and lighting designs

LED POOL LIGHTING COMPARATIVE PRODUCT MATRIX











| | CMP BRILLIANT WONDERS® | HAYWARD® COLORLOGIC® | PENTAIR® GLOBRITE® | SAVI MELODY/ JANDY NICHELESS | SR SMITH™ TREO |
|--|---|--|--|--|---|
| SUMMARY | Quick installation, designer flanges and Smart Sync™ technology | Installs in 1.5" pipe, compatible with Hayward control systems | Compatible with Pentair systems, different models for different pool types | Replaceable light cartridges, OEM sync available from SAVI | Low wattage light with optional advanded LED control system |
| IP68 Waterproof Disconnect | | | | | |
| Nicheless Installation | • | • | | • | • |
| Heat Conductive Light Body | • | | • | | |
| No Bonding or Grounding Required | • | • | • | • | • |
| Gunite, Vinyl or Fiberglass Installation | • | • | Special Niche Required | • | • |
| Soft Light Falloff, Smooth Blending | • | | | | |
| Wall or Floor Installation | • | • | | • | |
| Water Cooled | • | | • | | • |
| Bayonet Locking Installation | • | | • | | |
| PSN Reader's Choice Award | • | | | | |
| Retrofit in Most Pools | • | | | | |
| RGBW Technology | • | | • | • | |
| Bright & Efficient Cree® LEDs | | | • | | |
| Multiple brightness levels available | • | • | | • | |
| Dimmable (with upgraded controls) | | • | | • | • |
| White Only Available | • | • | | Jandy Only | • |
| Electrical* | 11W/8W, 12VAC | 23/13W, 12VAC | 15W, 12VAC | 14W, 12VAC | 5W |
| Cross-Platform Sync | Smart Sync™ | | | P, H or S Series (SAVI Only) | |
| Warranty | 3 Year (pro-rated) | 1 Year | 1 Year | 5 Year (pro-rated) | 3 Year |
| Designer Flanges | • | | | | |
| Beam Angle* | 140 Degree | | 100 Degree | 180 Degree | |
| Certifications | ETL | UL | UL | ROHS, ETL, CE | |

*per available OEM specifications



BRILLIANT WONDERS MARKETING SUPPORT

Print and Web Advertising
Interactive Product Displays
Extensive Trade Show Presence
Training Opportunities





ADVERTISING

Pool & Spa Marketing, Pool & Spa News, PEP Newsletter, Pool Pro Magazine, Aqua Magazine Print Ads







Custom Molded Products

INTRODUCING THE SMART SYNC" UNIVERSAL CONTROL for Brilliant Wonders' LED Waterfalls. With one control box, sync your CMP waterfall with LED products from CMP*, Pentair', Hayward* and Jandy*. Simple to install, and field-programmable with a built-in control dial.

The Brilliant Wonders* LED Waterfall is the premier lighted waterfall in the pool industry. Featuring a patent pending design and front-side serviceability, no other waterfall comes close. And now with the addition of the new Smart Sync* control, the best LED waterfall is even better.

CMP is committed to supporting pool professionals with premier products and support that set you up for success. Because when the difference is in the details, everything matters*.

www.c-m-p.com





ADDITIONAL PSN ADVERTISING

Pool and Spa News Masters of Design
Pool and Spa News Readers Choice Award
Virtual Backyard Interactive Pool











WEB ADVERTISING

Web banner ads
Virtual Backyard
Lead Generation Page
(c-m-p.com/brilliant)









PRODUCT DISPLAYS

Interactive Countertop Displays
Brand New Designs for 2015












NEW TRADE SHOW DISPLAYS


Interactive Hands On Displays

Waterfalls and Lights in Sync

Product Video Loops

Wet and Dry Product Displays











WEB SALES TRAINING


C-M-P.COM/NPA

New Product Announcements

Product Infographics

Supplemental Material Downloads









OTHER TOOLS

2016 Catalog
Updated Cut Sheets & Brochures
Product Photos & Videos
Product Presentations



BRILLIANT LED POOL & SPA LIGHTING . . .

The Brilliant Wonders © 1.5" nicheless LED pool and spa light is versatile, easy to install and designed to sell. Create a sense of drama and excitement in any pool with bright LED light and colorful shows. Illuminate a pool, accent a spa or showcase steps, swim-outs and spillovers. Unleash your creativity with this designer LED light that is sized to fit in virtually any location. With so much to offer in one light, the next pool you build should be brilliant.

PRODUCT FEATURES

- Bright & Efficient Cree® LEDs Outlast and Outperform Other Lights
- Installs in Gunite, Fiberglass & Vinyl Pools
- Non-Metallic Design: No Bonding, No Grounding
- Maximized LED Projection & Precise Beam Angle Minimizes Shadows
- · Full Color, Full Stainless and Color Accent Stainless Faceplate Options
- Small Size can Retro-fit and Replace Almost Any Nicheless Light



SIMPLE INSTALLATION & SERVICE

Installs in any 1.5" pool wall fitting and locks in place with a quarter-turn. Industry-first quick disconnect IP68 connection for rapid service, winterizing or replacement.



HIGH PERFORMANCE. ENERGY EFFICIENT.

Precise engineering delivers a perfect balance of brightness, energy savings and longevity. Over 50,000 hours of low voltage LED life saves customers' money and reduces service calls.



BUILT-IN CMP SMART SYNC™ TECHNOLOGY

Available with Smart Sync programming to synchronize with lighting and controls from major pool OEMs.



INTERCHANGEABLE DESIGNER FACEPLATES

Consumer-targeted designer faceplates completely hide the wall fitting and look great day or night. Available styles include seven full color faceplates, seven color accents and full stainless.







AVAILABILITY DATES

AVAILABLE IMMEDIATELY

1.5" LED RGBW Triple and RGBW Single Light in

both J and H Styles

1.5" LED Light in White

AVAILABLE LATE OCTOBER

Smart Sync Waterfall for all styles

1.5" 1.5" LED RGBW Triple and RGBW Single for P Style

NOVEMBER 2015

12" Smart Sync Laminar for all styles

JANUARY 2016

Smart Sync Bubbler for all styles





Brilliant Nonders LED LIGHTING